


wire

TRU-CHROME®: TWISTED, BRAIDED WIRE

**TRI-FLEX Twisted Wire**

Tri-Flex (3 strands) is spring-tempered, twisted leveling wire for early treatment stages. It bends readily and can accept great deflection before its limit is reached. It provides gentle force and will not unravel or fray when cut.

Shape	Size (inch)	Size (mm)	Package Contains	Order Number
Round Straight	.0155	(0.394)	10	E00175
Lengths (14")	.0175	(0.445)	10	E00176
	.0195	(0.495)	10	E00177
	.0215	(0.546)	10	E00178

**SUPRA-FLEX™ Twisted Wire**

Supra-Flex™ (6 strands) is cable-designed, initial stage arch wire with five exterior wires helically wound around a core wire. It can be flexed to a great degree without taking a set. It delivers constant uniform light force over a long period of time and does not fray when cut.

Shape	Size (inch)	Size (mm)	Package Contains	Order Number
Round Straight	.0155	(0.394)	10	E00179
Lengths (14")	.0175	(0.445)	10	E00180
	.0195	(0.495)	10	E00181
	.0215	(0.546)	10	E00182
	Round Spools (30')	.0155	(0.394)	10
	.0175	(0.445)	10	E00188
	.0195	(0.495)	10	E00189
	.0215	(0.546)	10	E00190

**FLEX-VIII™ Braided Wire**

- Flex-VIII™ (8 strands) is a braided wire for unscrambling and leveling
- Preformed arch

Shape	Size (inch)	Size (mm)	Package Contains	Order Number
Square	.016 x .016	(0.406 x 0.406)	10	E01400
Rectangular	.016 x .022	(0.406 x 0.559)	10	E01401
	.017 x .025	(0.432 x 0.635)	10	E01403
	.018 x .025	(0.457 x 0.635)	10	E01404
	.019 x .025	(0.483 x 0.635)	10	E01405